

# CO-LOCATION CABINET FRAMES



## Product Features

### Finish

- Durable black textured powder paint finish

### Structure

- 83" tall cabinet, with up to 44 U-Space of vertical capacity
- Frame constructed of rugged 13GA steel
- Ideal for data center environments
- Provisions for 4 ground lugs (1 supplied)
- Provisions for 1/2 or full height doors
- Maximum opening in the base of the cabinet
- Standard mounting locations for left or right opening doors
- Provisions for cable pass through for ganging situations.
- Fully welded for rigidity
- Built standard with perforated roofs
- Provisions for fans and cable entry on top
- Comes with tamper proof cover plates.
- Secure compartments for multiple customers

### Options

Co-location cabinet frames support the line of:

- Doors, full and half height
- Side panels, perforated or solid
- Mounting angles, full & half height
- Locks, push button, flush locks
- Cable Management System, full & half height
- Cover Plates
- Power Solutions
- Shelves
- Ganging kit
- Cooling fans

**Note:** All of our cabinets are fully customizable. If desired options are not listed, speak with your CableTalk representative. Co-location cabinets are available with 3 or 4 compartments upon request.

### Co-location Frames

Part No.	Description	Width (Inches)	Depth (Inches)	Height (Inches)	U-Space
CTC3-2436-CLP-B	24W x 36D x 83H frame flex top	24	36	83	44
CTC3-3036-CLP-B	30W x 36D x 83H frame flex top	30	36	83	44
CTC3-3042-CLP-B	30W x 42D x 83H frame flex top	30	42	83	44
CTC3-3047-16-CLP	30W x 47D x 83H frame flex top	30	47	83	44

Co-location frames do not come with casters or levelers.

### Co-location Components

Co-location cabinets can be assembled as 1 or 2 compartment units. Below are items for each scenario. Options on power bars are available.

		Frames	
		CTC3-2436-CLP-B	CTC3-3036-CLP-B
Use in 2 compartment cabinets	1/2 perf door with 10 push button	CTC3-24-0250PF-B	CTC3-30-0250PF-B
	Side panels, perforated, 2-4" cut outs	CTC3-36-13-CLP	CTC3-36-13-CLP
	Mounting angles, 37" high, tapped 10-32	CTC4-MA-22-50-B	CTC3-MA-16-50-B
	or cage nut 10-32	CTC4-MA-22C-50-B	CTC3-MA-16C-50-B
	Cable Manager, 83" high, 1/2 cover door	CTC3-CMS-37-B	CTC3-CMS-37-B
	Divider panel	CTC3-DIVD-2233-CLP	CTC3-DIVD-2833-CLP
	Floor panel	CTC-2436-43-B	CTC-3036-43-B
Castor plate (for floor panel)	CTC-48-24-B	CTC-48-30-B	
Use in 1 compartment cabinets	Full perforated door with 10 push button lock	CTC3-24-02PF-B	CTC3-30-02PF-B
	Side panels, perforated, 2-4" cut outs	CTC3-36-13-CLP	CTC3-36-13-CLP
	Mounting angles, 77" high, tapped 10-32	CTC3-MA-22-B	CTC3-MA-16-B
	or cage nut 10-32	CTC3-MA-22C-B	CTC3-MA-16C-B
	Cable Manager, 83" high with 1/2 cover	CTC3-CMS-37-B	CTC3-CMS-37-B
	Cover plate	CTC-54-B	CTC-54-B
	Power bar, 6 outlet, 7' cord	CTPBH-0619-B	CTPBH-0619-B
	Power bar, 6 outlet, 15' cord	CTPBH-0619-15-B	CTPBH-0619-15-B

