CableTalk®

Custom Data Center Solutions

IN-ROW AIR CONDITIONER
SERIES IR

3 TON UNIT

In-Row Configuration for Compact Footprint and Maximum Flexibility

CLIMATEWORX
MISSION CRITICAL CLIMATE CONTROL

COOLING MODES

- Water Cooled DX
- Air Cooled DX
- Glycol Cooled DX
- Chilled Water

CONFIGURATIONS

- Rear to Front Flow
- DX in R410A

COMPACT FOOTPRINT
The Series IR air conditioner's compact dimensions (12"x 42") minimizes floor space footprint.

MAXIMUM FLEXIBILITY
The Series IR installs entirely above floor, which is ideal for low ceiling and non-raised floor cooling configurations.

SPOT COOLING
Ideally suited to combat hot spots as a support to existing cooling systems.

ROW BASED COOLING
Positioned in the row, the Series IR performs well as both a stand alone air conditioner or in conjunction with our hot or cold aisle containment system.

DETAILS
- Variable capacity operation
- Air cooled DX is ideal for incorporating into existing systems
- 900W power supply for 66% redundancy
- Dual A-B power feed
- SS condensate drain pan
- Condensate management
- Remote temperature sensor

BLOWER MOTORS
Energy efficient axial fans are easy to access and are hot swappable for zero down time replacement.

CONTROL MODULE
Network compatible microprocessor controlled.

FILTERS
Aluminum washable 1" deep MERV 1 mesh filter. 20% efficiency.

12" wide x 42" deep x 83" tall

CableTalk
Custom Data Center Solutions

CLIMATEWORX
MISSION CRITICAL CLIMATE CONTROL

FOR ALL SPECIAL REQUIREMENTS, PLEASE CONTACT US

CABLETALK SYSTEMS

14 Chelsea Lane
Brampton ON, L6T 3Y4, Canada
Tel: (905) 799-2002
Fax: (905) 799-2003
1-800-267-7282

ISO 9001:2015

All ClimateWorx equipment is evaluated and accepted by a Nationally Recognized Testing Laboratory, NRTL accredited organization to UL 1995 standard.

BEMPRO
GLOBAL GROUP INC.

CableTalk Systems is part of the Bempro Global Group of companies.

COLE-CW-SIR24-F 2025.12.09